

Technical Specifications

	7. Power consumption: <1500 Watts
	B. Inclusions
	1. Rotors and accessories:
	a. 1 unit Swing out rotor with 4 round buckets to hold 4X 200 ml with lid
	• 1 set of 4 adapters to hold 4x 100 ml round bottom tubes
	• 1 set of 4 adapters to hold 50 ml conical tubes
	• 1 set of 4 adapters to hold 15ml conical tubes
	• 1 set of 4 adapters to hold 2 ml microtubes
	b. 1 unit 2-ml fixed angle aluminum/alloy rotor to hold 24-30 microtubes with 24-30 pcs adapters for 0.2mL, 0.25mL, 0.5mL microtubes
	• 30 adapters each for 0.2ml, 0.25 to 0.4ml and 0.5ml tubes
	c. 1 unit 15-ml fixed angle rotor to hold 30 tubes
	d. 1 unit 85 to 100-ml fixed angle rotor to hold 6 tubes
	e. 1 unit Swing out rotor with lids and carriers to hold 6 microplates
	2. 1 unit 2KVA UPS with AVR
	3. 10 cases of 500s 15ml conical tubes
	4. 10 cases of 500s 50ml conical tubes
	5. 4 pcs 100ml autoclavable plastic container with screw cap, wide mouth
	1. Shipping, installation by field technical specialist, and all materials needed for installation
	2. 2 years warranty on all parts and services
	3. Annual preventive maintenance and re-certification of equipment calibration for the duration of the warranty period
	4. Trainings on equipment operation, maintenance, and troubleshooting. Training should be good for 10-15 pax.
	5. Training certificates
	6. Equipment calibration certificates
IV. Standard Minifuge with adapters (1 unit)	A. Specifications
	1. Sample capacity: 0.2-2 ml
	2. Maximum speed between 5000-6000rpm
	3. Electrical requirement: 200-240V, 50-60 Hz
	B. Inclusions
	1. 1 unit 1.5/2.0 ml tube rotor
	2. 1 unit 0.2ml strip rotors for 16 tubes
	3. 1 set of 0.2ml tube adapters
	4. 1 set of 0.5ml tube adapters
	5. 1 unit Storage case for rotors and adapters
	6. 1 unit Tube rack for 0.2ml, 0.5ml and 2 ml tubes
	7. 1 unit AVR for Oven drier